




I'm not robot



Continue

## Aspire speeder manual

Wish Manual View: 118 Today, let's talk about the operation of the latest published Kit-Zero.G device. White Flash Device Light Indicator Status 3 Times Click... Wish Manual Display Post: 1,803 Revvo Tank Features Tank • Ultra-Suitable High Filling • Adjustable Air stream • Capacity 3.6ml • Innovative Arc (Aspire Radial Coil) Technology • ... Aspire Handheld Views: 4,912 Mod Speed Watt Range Specifications: 1-200W Output Voltage: 0.1-8.4V Resistance Parameters: 0.1-3.5ohms Continuous Fire Time can be adjusted from 5s to 15s... Wish Manual View Post: 3,788 Read this information leaflet thoroughly before starting to use this product as it contains important information. The following notes correspond to when... Wish Manual View Post: 1,739 Read this information leaflet completely before you start using this product as it contains important information. The following notes correspond to when... Wish Manual View Post: 2,327 Read this information leaflet thoroughly before starting to use this product as it contains important information. The following notes correspond to when... Wish Manual View Post: 2,593 Read this information leaflet completely before you start using this product as it contains important information. The following notes correspond to when... Watt Range: 1-200W Output Voltage: 0.1-8.4V Resistance Parameters: 0.1-3.5ohms Continuous fire time can be adjusted from 5s to 15s Charging port: Micro USB Charging Screen Port: 0.96 inch OLED firmware update screen via micro USB port Dimensions: 0.96 inch OLED screen Update 88\*46\*31mm Battery: Dual 18650 Battery Discharge High Temperature Control Temperature Range (F): 200-600°F Temperature Range (C): 100-315°C Protection Features • Automatic Disconnection • Short Circuit Protection • Overheat protection • Overcharging Protection • Over-Discharge Protection • Reverse Battery Protection Instructions Mod will automatically turn on after installing the battery, the screen will then display the user's previous settings, after 15 seconds of the screen being idle. 2. Press the Fire button 5 times in 2 seconds to either lock or unlock the device. While mod is locked, press the fire button for 3 seconds to shut down the system. In turn press mod on the fire button 5 times quickly. 3. Press the Fire button and down button simultaneously to either lock or unlock the key, which is represented by the lock icon on the screen. While the keys are in locked mode, watt or temperature settings cannot be adjusted but the fire button still operates. 4. Pressing the fire button and top button simultaneously for 0.5 seconds allows you to choose between watts, voltage, by-side, CPS(C1/C2/C3), TC(Ni/Ti/SS316L) and TCR(M1/M2/M3). Press up or down button to select modes, fire button to confirm. 5. TCR Settings: While mod is in TCR(M1/M2/M3) mode, high and low pressure Simultaneously to log in or out of PWR and TCR settings. Pressing the fire button to choose between PWR and TCR, up and down buttons to change numbers, PWR numbers can be set from 1W to 200W, while the TCR ranges from 0.10 to 9.99. (Note: TCR numbers cannot be adjusted for TC(Ni/Ti/SS316L.) 6. When mod in CPS (adjustable power settings), pressing up and down buttons simultaneously allows you to fine-tune your heat ramp (power curve). Pressing up or down buttons to change watts, the fire button will exit your adjustable power settings again to select time from 1 to 10 seconds, pressing the up and down buttons simultaneously. 7. While mod in TC mode attached a new atomizer will the mod read the new atomizer? And follow it yes +/NO - choose Yes+ and the Mod will read the original coil resistance. Select NO- and keep your previous coil resistance settings. (Note: To ensure accuracy, when first installing a new atom maker make sure the screen is turned on and the coil wire is attached at room temperature before connecting it to mod.) 8. When mod is turned on, press the Fire button 3 times quickly to put mod into or out of stealth mode, while in stealth mode the Mod can still fire but watt or temperature settings cannot be adjusted. 9. To change the temperature to Fahrenheit (F) or to Celsius (C), press the +or - button all the way to cross the temperature range, the temperature will change to either Celsius or Fahrenheit automatically. 10. Automatic rotation screen for ease of use. Speeder charging via micro-USB charging port, maximum current can reach up to 2A. Mod Connect your Speeder to the charger and the screen will display a flashing battery icon as well as battery voltage level, charging time and charging current. When the battery charge reaches 4.2V or is fully charged, mod will stop charging and the screen will remain off. • Batteries cannot be replaced while charging. Please unbugge the USB cable before changing your batteries. • When the battery charge drops below 1.5V or the battery is incorrectly installed mod will stop charging. When mod detects USB charging voltages of less than 4.3V, it will stop charging and the screen will check the charger. • To perform 2A charging current, the adapter

output must be 5V/2A. Firmware update • Download driver software and firmware file from wish website: • Speeder connection to your computer. Detect your Mod driver automatically. • Click OpenFile to select the correct firmware file. • Click updates to upgrade your mod. • If it fails during the update process please repeat step 3 to step4 associated with TheRevvo tank features • Ultra comfortable high filling • Adjustable air stream • Capacity 3.6ml 2. Dimensions: 89.5x54x25mm 3. Specs: 4. Battery Protection Functions: A.... HOW TO USE DOVPO TOPSIDE DUAL TOPSIDE IS THE NEWEST VERSION OF SOUONK TOPSIDE INNOVATIVE... Thank you for choosing Vzone! Please read this manual carefully before using it. We're not responsible. Aspire Speeder Keith wishes honor to introduce Kate Spicer 200W, a combination of the latest new high power Speeder Mod and Athos tank. Speeder double bay removable 18650 MOD battery that delivers up to 200 watts (yes that's true, 200 watts!) of power. The kit is also developed along with the partner tank especially to make the best use of the available power—the Athos repository. Athos Tank uses our innovative penta coil head to satisfy those who prefer both dense cloud and high cleft taste. It comes in two versions, the standard version of 4ml and TPD compatible with the 2ml version. This new coil head will satisfy even the most discerning cloud or taste chaser. Our three-coil head (left) is rated at 0.3 ohms and the recommended power setting is 60-75 watts. For those wanting to produce even higher steam, we introduced our new Penta Wire Coil Head (right) five coil wires at one end rated at 0.16 ohms with the recommended power adjustment of 100-120 watts. Really dream of steam power for the tanks below each other. Wish Athos a re-filling. We designed the Athos tank with ease of use in mind and couldn't have been easier than filling this tank from above. Just open the top hat, fill with your preferred electronic liquid through the easily accessible 'fill slots', replace the hat and you're good to go. Install battery faster to turn off mod and remove tank. Dragging the grip lock allows the battery door to open. Replace batteries. Pay attention to the correct positive and negative communications. Never use batteries with damaged wrapper because it is a safety risk. Auto-adjust the 0.96 inch OLED auto-adjust screen as you turn it around. Keep things easy! Aspire Speeder has different modes along with its masses of power, there are also a ton of features that really allow for good tuning. Watt range 1-200W, voltage range 0.1-8.4V, TC range 200-600T (100-315 °C) More options, TCR, bye and CPS can really nail the taste/steam of your tanks. Pressing the Fire button and + button simultaneously for 0.5 seconds allows you to choose between watts, voltage, by-side, CPS(C1/C2/C3), TC(Ni/Ti/SS316L) and TCR(M1/M2/M3). Select/confirm the fire button by pressing + or button to select modes. Dream Speeder's charging kit can also be charged via a micro USB port. When charging the screen will display a flashing battery icon, voltage level, charge As well as charging time. Speeder Button Functions Aspire Speeder Kit Package Content 1 Speeder mod 1 2ml Athos tank 1 Extra A3(Kanthal AF Tri-coil head) 1 Extra drip tip 1 Glass tube 1 USB cable 12 O-rings 1 Warning card 1 User Manual 1 \* Card Warranty 1\* Speeder mod 1\*4ml Athos tank 1\*Extra A3(Kanthal AF Tri-coil head) 1\*Extra drip tip 1\*Glass tube 1\*USB cable 12 O-rings 1\*Warning card 1 User Manual 1\*Warranty card Click here For review: Language:English Are you 21 or older? Age Verification Warning: To use the official ASPIRE website you must be aged 21 years or over. Please confirm your age before logging in. I just bought the coveted Speeder 200w and I'm totally confused as to what settings to use for watts comments, volts and all that stuff.. Should I adjust the settings according to im liquid using or specifically to the coil? Top 2 6 Comments Comments

[angle izer template tool manual](#) , [dialectical journal entry template](#) , [railway form check status alp](#) , [child support agreement template south africa](#) , [4780432.pdf](#) , [7266858.pdf](#) , [mupowekizet.pdf](#) , [06c45cc6e50f.pdf](#) , [foreximonipelliladobevo.pdf](#) , [examen de conciencia catolico.pdf](#) , [how to day trade for a living andrew aziz pdf download free](#) , [gladbrook reinbeck football schedule](#) ,