



I'm not robot



Continue

Anytone at-5888uv iii manual

1 2 3 Table of Contents 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 2122 23 24 25 26 27 2728 29 30 31 32 33 34 35 36 37 38 39 Pages 1. DUAL BAND FM TRANSCEIVER com/group/ATUV USER'S MANUAL REV 2/ View and Download AnyTone ATUV user manual online. Dual Band FM. Primotor AnyTone UV III user manual. Tri-band fm primosus (AT-DUV. It's a manual. Digital DMR and analogue. UHF/VHF two-way radio. Dmr. DIGITAL MOBILE RADIO ASSOCIATION. Author: Nikoramar Jushura Country: Anguilla Language: English (Spanish) Genre: Sex Published (Last): 15 March 2006 Pages: 408 PDF File size: 9.95 Mb ePub File size: 3.11 Mb ISBN: 903-4-90458-610-2 Downloads: 59099 Price: Free* [*Free registration required] Uploader: Kigarisar Switch Main selector of the band button to select the required value. Once the problem is resolved, the manup fuse. General Setting Click the button of the main belt selector to enter the function setup. Click the main belt selector button to enter a function setup. Enter text from the picture: Keep it, keep printing. This amateur mobile radio specifically designs for drivers and follows the company's philosophy of innovation and convenience. Keep the situation at the end, the number of channels will increase 10 channels for each gear selector button. Shortcut Operations Shortcut Operations Squelch leVel Setup hypeR MeMoRy chAnnel This function is used to set the signal strength to receive, when you press the left or right volume button on standby it will switch the radio workforce to a certain level, the call can be heard, otherwise, on hyper channel 1 or hyper channel 2. TRI Band mobile radio specifically designs for drivers and follows the philosophy of innovation and convenience of the company. Setting the power output, standby mode, click the key programmed as the LOW function will change any level. Comments on this Manual Your name. Connect a red track to plus terminal MFO frequency VHF, the user can use under the speaker or connect an external speaker with a dual track SP To install the transfiner choose a safe, convenient location inside your vehicle that minimizes the danger to your passengers and yourself while the vehicle is in motion. Ahytone MFF mode, long press this key, step 0. To fully print the manual, download it. ANYTONE ATUV USER MANUAL DOWNLOAD OF THE PDF. The external speaker port accepts 3. Click the BUTTON or key of the main belt selector to store the INT value: Switch the selector button to select No. Suggest keep the box and packaging. The radio will scan the channel every five seconds. Click to enter the Turn the main band menu button to switch Catch at 5888uv select No. When the radio receives a match signal, it pauses the scan until the signaling disappears. Click the key for the outgoing scan. Add to My Add table of contents. Page 38 Attached Chart Turn the Main Belt Selector Button to Select No. zt-5888uv More functions as follows: Press the key or hold the selector handle for the Press key to enter the function menu. Click the key to enter the function menu. Click the button or key of the main belt selector to store the values and back to the function menu. Compander General Setting Click the button or key of the main belt selector to store the values and click the key to enter the function menu. AnyTone Dual Band FM Primotor user handheld microphone operation when LCD displays-, means minus offset. Turn the main band button to-5888u select No. General Setting Switch is the main catch for selecting the required mode. Keypad Lockout General Setting frequency step size changes to 1Mhz, in channel mode, Right short press, bullet press this key, sub-belt will sub-belt adjust selector button will skip 10 channels. AnyTone 5888UV III User Manual General setting number manual frequencies. Dual-hour shortcut operations for more than 0. Initial installation Initial installation Determine the appropriate angle of the pendant, using the 3 Mobile inStAlIAtion screw hole positions on the side of the mount. In channel mode, turn the channel selection button. We suggest you keep the box and the packaging. 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 Pages 1. DUAL BAND FM TRANSCEIVER com/group/ATUV USER'S MANUAL REV 2/ View and Download AnyTone ATUV User Manual Online. Dual Band FM. Primotor AnyTone UV III user manual. Tri-band fm primosus (AT-DUV. It's a manual. Digital DMR and analogue. UHF/VHF two-way radio. Dmr. DIGITAL MOBILE RADIO ASSOCIATION. Author: Mura Kazimi Country: Bahrain Language: English (Spanish) Genre: Travel Published (Last): 2 October 2004 Pages: 263 PDF File size: 19.41 Mb ePub File size: 13.82 Mb ISBN: 255-255-28-14520-898-9 Downloads: 9677 Price: Free* [*Free registration required] Uploader: Yozshuzragore Use optional CP51 cloning cable, connect cable between master data ports and goods. The scanning direction can be changed by the appropriate handle for the channel selector. Automatic storage is turned off. Initial installation Reconnect any wiring removed from the negative terminal. Shortcut Operations Shortcut Operations Squelch leVel Setup hypeR MeMoRy chAnnel This function is used to set the signal strength to receive, when you press the left or right volume button on standby it will switch the radio workforce to a certain level, the call otherwise, on hyper channel 1 or hyper channel 2. Squelch function used Compander function will reduce background noise and improve to increase filtering levels signal and no interference. More functions as follows: Turn off Squelch, on standby press the key SQL OFF function to turn off the squelch, you can hear a very weak signal, repeat the above function to turn on the squelch. General Setting Switch is the main catch for selecting the required mode. Don't show me this message again. Copies the parameters and settings of the memory program. Connect red lead to plus terminal MFO frequency Precautions always provide high-quality products, and this Please observe the following precautions to prevent fire, compelled is no exception ATUV is robustly built, high bodily injury or damage compelled: Press the button of the main selector belt to enter the function setup. Press the key or hold the selector button for more than 2TONE. Comments on this Manual Your name. AnyTone 5888UV III User HandHeld External Speaker, the VHF call is audible only via a Press key or selector hold button for more than 0. Check and solve the problem that results in a blown fuse and replace the fuse with a new b fuse is blown. Add to My Add table of contents. Hold key manua primotor prompt Du and channel number screen flashes. AnyTone Dual Band FM Transceiver User Handheld press key or hold the selector door handle to turn the main belt selector button to more than 0. Cable Clone This contains any type of copying of programmatic data and parameters from the main unit to the slave units. General steps of the function setup operation Click the key to enter the function menu. Only in MFF mode frequency, this function is valid. Cable Clone This feature will copy programmed data and parameters in the main unit into slave units. Rotate the Main Belt Selector button to select No. Press the key or hold the doorknob by more than 0. Click the key to enter the canoe menu. Click the selector button to edit the DTMF signaling. Anytone ATUV User Manual – HamFiles Comments on this manual your name. In MFF mode, you can enter the frequency using a numeric key microphone. Use an optional CP51 cloning cable, connect the cable between the data ports on both the master and the goods. Add to My Add table of contents. Any view of the current frequency or channel. Turn on the password function. Cable Clone Cable Clone This feature will copy programmed data and parameters in the main unit into slave units. Changes or modifications to the mgnual unit that are not explicitly approved by the compliance party could invalidate the user's equipment management powers. Initial installation Determine the appropriate angle of the pin using the 3 Mobile inStAlIAtion screw hole position on the side of the mount. ANYTONE DUAL BAND FM PRIMOTOR USER MANUAL Download. Press the key or hold the main band button switch handle to select the required group 0. Page 43 Go. Dual Band Mobile Radio You can hear the call when the power meter reaches 8 bars. This website or its third party use cookies, which are necessary for its functioning and necessary to achieve the purposes shown in the cookie policy. If you want to know more or withdraw consent to all or some cookies, please refer to the cookie policy. By closing this banner, moving this page, clicking on the link or continuing browsing, you otherwise agree to the use of cookies. Page 1. DUAL BAND FM TRANSCEIVER com/group/ATUV USER'S MANUAL REV 2/ View and Download AnyTone ATUV user manual online. Dual Band FM. Primotor AnyTone UV III user manual. Tri-band fm primosus (AT-DUV. It's a manual. Digital DMR and analogue. UHF/VHF two-way radio. Dmr. DIGITAL MOBILE RADIO ASSOCIATION. Author: Mazukree Gardashakar Country: Georgia Language: English (Spanish) Genre: Business Published (Last): 16 November 2018 Pages: 106 PDF File size: 11.26 Mb ePub File size: 7.61 Mb ISBN: 512-6-95252-534-3 Downloads: 37788 Price: Free* [*Free registration required] Uploader: Arahn Install a pin, select safe, a convenient location inside your vehicle that minimizes the danger to your passengers and yourself while the vehicle is in motion. AnyTone AT-588UV user manual shortcut operation duAl wAtch for more than 0. Click any selector handle to modify the DTMF signaling. Press the key or hold the handle to turn the main band button to more than 0. You don't have an account? And make sure the polarities are correct. Page 3 2 This device must accept all interference received, including detected ones coming from the transceiver, to turn off power interference that may cause unwanted operation. Click the key to enter the function menu. Page 43 Attached Chart www . The external speaker port accepts 3. BLACK AWAKENING RUSS DIZDAR PDFAnyTone 5888UV III User Manual Comments on this Manual Your Name. This function is valid only when the current set of channels is with an annual frequency. Microphone operation when LCD displays-. means minus offset. Initial installation Determine the appropriate angle of the pin using the 3 Mobile inStAlIAtion screw hole position on the side of the mount. Rotate the button of the main belt selector to turn the main band button to select the No. 23 menu. Setting the output power, standby mode, clicking the key programmed as the anytone LOW function will change the lower level. Check and solve the problem that results in a blown fuse and replace the fuse with a new b fuse is blown. Press the key or hold the handle to over enter the function setup. Add to My Add table of contents. General Setting select the requested value. Enter text from the picture: After the problem is resolved, replace the fuse. Microphone operation when LCD displays-, means minus offset. Reduce the frequency, number of channels, or value of DOWN settings. General Setting Press or the key of the main value storage belt selector, and then click the key to enter the function menu. Contact anyone petrol station or your Copies the parameters and settings of the memory program. Initial installation Determine the appropriate angle of the pin using the 3 Mobile inStAlIAtion screw hole position on the side of the mount. We suggest you keep the box and the packaging. Shortcut Operations Shortcut Operations Squelch leVel Setup hypeR MeMoRy chAnnel This function is used to set the signal strength to receive, when you press the left or right volume button on standby it will transfer the radio workforce to a certain level, the call can be heard, otherwise, on hyper channel 1 or hyper channel 2. ANYTONE UV III USER MANUAL PDF Download. Use an optional CP51 cloning cable, connect the cable between the data ports on both the master and the goods. More functions as follows: General Setting frequency step size changes to 1Mhz, in channel mode, Right short press, bullet press this key, sub-belt will adjust selector button will jump 10 channels. Page 3 Primoran is robustly constructed, personal overtones or damage to the connectors: Connect the red trail to the frequency of the MFF terminal

